



LW2 SERIES

Architectural Linear Ambient LED Luminaire

Fixture Type:

Job Information:

SPECIFICATIONS:

LED MODULES:

- High performance linear configured LED module boards.
- Each board consists of multiple mid-power, high efficacy LEDs in a precise layout eliminating the need for supplemental heat sinking.
- The boards produce an even and diffuse light which maximizes optical efficiency.
- Compatible with the dimming performance of the LED driver.
- Color temperatures available: 3000K, 3500K and 4000K.
- Upon request: 5000K.

LED DRIVERS:

- Factory programmable constant current LED power supply.
- Multiple standard drive current outputs (factory set by Mercury) are cataloged with their corresponding lumen package offerings. Upon request, custom drive current outputs and lumen packages are available.
- Note: Certain cataloged lumen packages may be provided with a non-programmable constant current LED power supply at Mercury's discretion. Contact factory if critical.
- Universal voltage input, 120V-277V, 50HZ-60HZ.
- Specification grade dimming down to 1% on 0-10V dimming controls.

LED LUMEN PACKAGES:

- Cataloged standard lumen packages. See attached chart for full details.
- Custom lumen packages pre-set are optional with programmable drivers only. Contact factory for details.

HOUSING:

- Fabricated from heavy gauge code grade cold rolled steel with housing ends welded into place.
- White polyester powder coating finish for long lasting durability.
- Sufficient electrical knockouts are provided on the housing back and ends.

DIFFUSER:

- Architecturally-curved profile design.
- Extruded from custom formulated high transmission acrylic material.
- Linear ribbing for high LED performance.

STANDBY LIGHTING OPTION:

- Self contained module, 10W or 12W as specified. Battery backup upon loss of power. Available 4Ft. modules only.

OPTIONAL INTEGRAL OCCUPANCY SENSOR:

- Self-contained sensor mounts directly to luminaire.
- Passive infrared (PIF) technology for individual luminaire control.
- On/Off control with optional delay features.
- See ordering matrix for available sensors.

INSTALLATIONS:

- May be installed in any direction, individually or in continuous run applications.
- May be surface mounted or suspended.
- End knockouts for surface conduit entry.

CERTIFICATE OF SAFETY COMPLIANCE AND LISTINGS:

- Luminaire: UL and CUL listed 1598 and bears their label. Suitable for damp locations.

WARRANTY:

- 5-year limited warranty is standard. Special 10-year warranty available on a job-to-job basis. Complete LED warranty terms available at www.mercltg.com.
- Actual performance may differ as a result of end-user environment and application.
- Most LED luminaires are suitable to operate in ambient temperatures from -20C (-4F) to 25C (77F).
- The following exclusions apply: Luminaires with optional standby lighting option, integral lighting controls options, or wireless control options. Consult factory.
- LM-79 testing was measured under a controlled 25C (77F) ambient operating temperature.

FEATURES:

- Shallow form linear ambient LED luminaire.
- Architecturally-curved acrylic diffuser evenly surrounds the LED light source enabling a very wide and near-perfect light distribution.
- Compact design complies with all ADA requirements for public areas.
- Custom formulated high diffusion acrylic material allows for maximum light transmission while eliminating pixilation and hot spots.
- Nominal 2Ft. or 4Ft. long modules.
- Digital LED technology provides high efficacy and energy efficiency.
- Multiple power and light levels are offered as standard to allow meeting design and energy needs per application. Custom factory set levels available on request.
- Lumen maintenance; Reported L70 (hours) & L80 (hours) > 60,000.
- CRI greater than 80.
- Fixture lumens per watt ratios up to 151.
- American Made.



LW2 SERIES

ORDERING DATA:

Example: LW2-4-3800-35K-HTA-1%-UNI-EM10

SERIES	NOMINAL LENGTH (FT)	NOMINAL LUMENS	COLOR TEMP	DIFFUSER	DRIVER	VOLTAGE	OPTIONS
LW2	2 24" Length	24"L	30K	HTA High Transmission Acrylic	1% 0-10V 1% Dimming	UNI	Standby Modules EM10 EM12 Available 4ft. Modules Only Optional Integral Occupancy Sensor O4 Wattstopper FS-155-1 mounts internally with only the PIF dome visible. O7 Leviton ZLS05-ILW mounts internally with only the PIF dome visible
		2100	35K				
	4 45" Length	2300	40K				
		2500	50K Upon Request				
	45"L	3400					
		2100					
		3800					
		4500					
		5000					
			6700				
		9400					
		XXXX	Custom Lumen Package. Contact Factory.				

LUMEN PACKAGE


Series	Nominal Length (FT)	Nominal Lumen Package	Color	Fixture Power (W)	Delivered Lumens	Fixture LPW
LW2	2					
		2100	3000K	15	1991	133
		2100	3500K	15	2048	137
		2100	4000K	15	2113	141
		2100	5000K	15	2114	141
		2300	3000K	16	2215	138
	2300	3500K	16	2279	142	
	2300	4000K	16	2353	147	
	2300	5000K	16	2355	147	
	2500	3000K	18	2382	132	
	2500	3500K	18	2452	136	
	2500	4000K	18	2531	141	
	2500	5000K	18	2534	141	
	3400	3000K	25	3247	130	
	3400	3500K	25	3348	134	
	3400	4000K	25	3455	138	
3400	5000K	25	3466	139		

Series	Nominal Length (FT)	Nominal Lumen Package	Color	Fixture Power (W)	Delivered Lumens	Fixture LPW
LW2	4					
		2100	3000K	14	1997	143
		2100	3500K	14	2050	146
		2100	4000K	14	2110	151
		2100	5000K	14	2110	151
		3800	3000K	26	3640	140
	3800	3500K	26	3743	144	
	3800	4000K	26	3862	149	
	3800	5000K	26	3862	149	
	4500	3000K	31	4263	138	
	4500	3500K	31	4386	141	
	4500	4000K	31	4527	146	
	4500	5000K	31	4529	146	
	5000	3000K	35	4764	136	
	5000	3500K	35	4903	140	
	5000	4000K	35	5061	145	
	5000	5000K	35	5063	145	
	6700	3000K	50	6389	128	
	6700	3500K	50	6585	132	
	6700	4000K	50	6796	116	
	6700	5000K	50	6818	136	
	9400	3000K	73	9171	126	
	9400	3500K	73	9406	129	
	9400	4000K	73	9561	131	
9400	5000K	73	9769	134		

PHOTOMETRICS:

All photometric reports are available at www.mercltg.com.

CROSS SECTIONS:



HANGING ACCESSORIES

PART #	DESCRIPTION	PART #	DESCRIPTION
R5PF-100	Round 5" power feed canopy, Hanging hardware, 100" long 1/16" cable.	VH-XX	"V" Hanger w/XX= 48"L or 72"L Chain & "S" Hook
R5-100	Round 5" canopy, Hanging hardware, 100" long 1/16" cable.	CPYS-1	S-1 Single Stem 5" Dia. Canopy
R2-100	Round 2" canopy, Hanging hardware, 100" long 1/16" cable.	STMXX	XX= 12"L, 24"L, 48"L Stem/ 3/8" IPS-5/8" OD
S5PF-100	Square 5" power feed canopy, Hanging hardware, 100" long 1/16" cable.	Other cable lengths available.	
S5-100	Square 5" canopy, Hanging hardware, 100" long 1/16" cable.		
S2-100	Square 2" power feed canopy, Hanging hardware, 100" long 1/16" cable.		

Actual wattage may differ by +/- 5% when operating between 120V-277V +/- 10%.



Detail

